



2137 Roosevelt Avenue · Racine, WI 53406 · Phone: (262) 633 – 3703 · Fax (262) 423 – 6743

www.WindowWellSupply.com

FREEDOM EGRESS WINDOW

DWS-4848



- All vinyl frame is maintenance free – No painting or rusting
- Window is poly-wrapped before pour to prevent any concrete getting on window
- Sashes are removable from the inside
- All egress sizes below have a minimum unobstructed opening of 5.7 sq./ft.
- Available in full and nominal wall thickness (8”, 10”, and 12” walls – No pouring bucks)
- All styles below operate without intruding into the areawall
- 5/8” insulated Low-E glass is standard – U-value of 0.33
- Sashes are double weather-stripped to protect from external weather infiltration
- Reversible if poured incorrectly – Header, jamb and sill parts snap-in for correction
- Half screen is removable from the inside
- Fully braced to support window during the concrete pour

Specifications

	Frame Dimension (Outside):	48” wide x 48” high
	Net Clear Opening A*:	20” wide x 44 1/4” high (6.14 sq. ft.)
DWS-4848	Net Clear Opening B**:	44 1/2” wide x 44 1/4” high (13.67 sq. ft.)
	Net Clear Glass Area:	21 9/16” wide x 42 3/4” high/per sash (6.4 sq. ft./sash -or- 12.8 sq ft./window)

*Sash opened in the normal inward operating position

**Both sash and screen removed from the frame

