

FREEDOM EGRESS WINDOW



DWS-4848

FEATURES

- All vinyl frame is maintenance free—No painting or rusting
- Window is poly-wrapped before pour to prevent any concrete getting on window
- Sashes are removable from the inside
- All egress sizes below have a minimum unobstructed opening of 5.7 sq./ft.
- Available in full and nominal wall thickness (8", 10", and 12" walls – No pouring bucks)
- Half screen is removable from the inside
- All styles below operate without intruding into the areawall
- 5/8" insulated Low-E glass is standard – U-value of 0.33
- Sashes are double weather-stripped to protect from external weather infiltration
- Reversible if poured incorrectly – Header, jamb and sill parts snap-in for correction
- Fully braced to support window during the concrete pour

SPECIFICATIONS

Solar Heat Gain Coefficient – 0.24

Visible Transmittance – 0.45

Condensation rating – 64

FrameDimension(Outside):

48"widex48"high

NetClearOpeningA*:

20"widex44 1/4"high(6.14sq.ft.)

Net Clear Opening B**:

44 1/2" wide x 44 1/4" high (13.67 sq. ft.)

NetClearGlassArea:

219/16"widex423/4"high/per sash

(6.4sq.ft./sash -or- 12.8 sq ft./window)

*Sash opened in the normal inward operating position

**Both sash and screen removed from the frame

