

Tilt & Turn Egress Window



TTW-3042

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 30" Wide x 42" High

Opening for Egress: Width: 24" Wide
Height: 36 ¾" high (6.12 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 21" x 33"

Visible Light Area: 4.81 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3048

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 30" Wide x 48" High

Opening for Egress: Width: 24" Wide
Height: 42 ¾" high (7.12 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 21" x 39"

Visible Light Area: 5.68 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3054

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 30" Wide x 54" High

Opening for Egress: Width: 24" Wide
Height: 48 ¾" high (8.12 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 21" x 45"

Visible Light Area: 6.56 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3060

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 30" Wide x 60" High

Opening for Egress: Width: 24" Wide
Height: 54 ¾" high (9.12 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 21" x 51"

Visible Light Area: 7.43 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3072

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 30" Wide x 72" High

Opening for Egress: Width: 24" Wide
Height: 66 ¾" high (11.12 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 21" x 63"

Visible Light Area: 9.18 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3242

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 32" Wide x 42" High

Opening for Egress: Width: 26" Wide
Height: 36 ¾" high (6.63 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 23" x 33"

Visible Light Area: 5.27 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3248

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 32" Wide x 48" High

Opening for Egress: Width: 26" Wide
Height: 42 ¾" high (7.71 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 23" x 39"

Visible Light Area: 6.22 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3254

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 32" Wide x 54" High

Opening for Egress: Width: 26" Wide
Height: 48 ¾" high (8.80 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 23" x 45"

Visible Light Area: 7.18 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3260

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 32" Wide x 60" High

Opening for Egress: Width: 26" Wide
Height: 54 ¾" high (9.88 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 23" x 51"

Visible Light Area: 8.14 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3272

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 32" Wide x 72" High

Opening for Egress: Width: 26" Wide
Height: 66 ¾" high (12.05 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 23" x 63"

Visible Light Area: 10.06 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3636

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 36" Wide x 36" High

Opening for Egress: Width: 30" Wide
Height: 30 ¾" high (6.40 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 27" x 27"

Visible Light Area: 5.06 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3642

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 36" Wide x 42" High

Opening for Egress: Width: 30" Wide
Height: 36 ¾" high (7.65 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 27" x 33"

Visible Light Area: 6.18 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3648

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 36" Wide x 48" High

Opening for Egress: Width: 30" Wide
Height: 42 ¾" high (8.90 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 27" x 39"

Visible Light Area: 7.31 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3654

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 36" Wide x 54" High

Opening for Egress: Width: 30" Wide
Height: 48 ¾" high (10.15 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 27" x 45"

Visible Light Area: 8.43 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3660

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 36" Wide x 60" High

Opening for Egress: Width: 30" Wide
Height: 54 ¾" high (11.40 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 27" x 51"

Visible Light Area: 9.56 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-3672

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 36" Wide x 72" High

Opening for Egress: Width: 30" Wide
Height: 66 ¾" high (13.90 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 27" x 63"

Visible Light Area: 11.81 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.

Tilt & Turn Egress Window



TTW-4848

FEATURES

- Interior: white, Exterior: white
- Available in right or left in-swing
- ROTO hardware
- 2 ¾" (70mm) Profile depth
- Backstop gasket system with two sealing levels
- Glazing thickness 15/16" (24mm)
- Tested burglar resistance class RC2
- 5 chamber system as standard combination
- Energy Efficient – Helps regulate indoor temperatures, reducing heating and cooling costs.
- Tilt inward for ventilation or fully open like a casement window for easy access and cleaning.
- Double Glass – Enhances insulation, improves safety, and reduces outside noise.
- Double Pain Argon Filled, 4/16Ar/4one
- Premium Aluplast 4000 Frame – Made from high-quality uPVC for weather resistance and minimal maintenance.
- Sleek & Modern Design – Complements any residential or commercial space with a clean and stylish look.

SPECIFICATIONS

Net Clear Opening:

Frame Dimension: (Outside) 48" Wide x 48" High

Opening for Egress: Width: 42" Wide
Height: 42 ¾" high (12.46 sq. ft.)

U-factor (U.S. / I-P): 0.23

Solar Heat Gain Coefficient: 0.34

Visible Transmittance: 0.51

Visible Light Dimensions: 39" x 39"

Visible Light Area: 10.56 sq. ft.

Air Leakage (U.S. / I-P): ≤0.01

16mm Aluminum Spacer

OITC = 0.26 psf

STC = 0.31 psf

CR = 0.65 psf

Design Pressure = 70.18 psf

Air Infiltration = 0.02 cfm/sf

Water Penetration Resistance = 12.11 psf

PERFORMANCE CLASS: AAMA/WDMA/CSA
101/I.S.2/A440-11 testing.