

Freedom In-swing Argon Gas Egress Window



FEATURES

- | | |
|--|---|
| <ul style="list-style-type: none"> • Argon gas filled with U-factor of 0.27 • Meets UBC & IRC-2000 codes for Egress (See dimensions below) • Available in full and nominal wall thickness (Attach 2" extension for 10" wall) • Welded sash with powder-coated handles for ease of operation • Fully braced and wrapped for poured wall installation | <ul style="list-style-type: none"> • All Vinyl frame and sash are maintenance free – No painting or rusting • 3/4" insulated Low-E glass and argon gas standard for added thermal efficiency • Sash is double-weatherstripped to protect from outside weather infiltration • Full screen is removable from the inside • Available in standard and custom sizes |
|--|---|

SPECIFICATIONS

Net Clear Opening Formulas:

· *Opening Width* = *Window Width* – 6.875

· *Opening Height* = *Window Height* – 4.125

· *Net Clear Opening Square Footage* =
$$\frac{[\text{Opening Width in inches}] \times [\text{Opening Height in inches}]}{144}$$

Net Glass Area Formulas:

· *Glass Width* = *Window Width* – 6.625

· *Glass Height* = *Window Height* – 6.625

· *Net Glass Square Footage* =
$$\frac{[\text{Glass Width in inches}] \times [\text{Glass Height in inches}]}{144}$$