

SPECIFICATIONS

Freedom Egress Window

Sliding egress window. Model DWS-4848 (48" × 48").
All-vinyl, maintenance-free frame with standard insulated Low-E glass.



Features

- All-vinyl frame is maintenance-free — no painting or rusting.
- Window is poly-wrapped before the pour to prevent any concrete from getting on the window.
- Sashes are removable from the inside.
- All egress sizes below have a minimum unobstructed opening of 5.7 sq. ft.
- Available in full and nominal wall thickness (8", 10", and 12" walls — no pouring backs).
- Half screen is removable from the inside.
- All styles operate without intruding into the areawall.
- 5/8" insulated Low-E glass is standard — U-value of 0.33.
- Sashes are double weather-stripped to protect from external weather infiltration.
- Reversible if poured incorrectly — header, jamb, and sill parts snap in for correction.
- Fully braced to support the window during the concrete pour.

Specifications

Solar Heat Gain Coefficient: 0.24

Visible Transmittance: 0.45

Condensation Rating: 64

Frame Dimension (outside): 48" wide × 48" high

Net Clear Opening A*: 20" wide × 44¼" high (6.14 sq. ft.)

Net Clear Opening **: 44½" wide × 44¼" high (13.67 sq. ft.)

Net Clear Glass Area: 21 9/16" wide × 42¾" high per sash (6.4 sq. ft. per sash — or — 12.8 sq. ft. per window)

**Sash opened in the normal inward operating position.*

***Both sash and screen removed from the frame.*