

SPECIFICATIONS

Freedom In-swing Argon Gas Egress Window

Welded all-vinyl in-swing egress window with insulated Low-E glass and argon gas. Available in four standard sizes — and custom.



Features

- Meets UBC & IRC-2000 codes for egress (see dimensions below).
- Available in full and nominal wall thickness (attach 2" extension for 10" wall).
- Welded sash with powder-coated handles for ease of operation.
- Available in standard and custom sizes.
- Fully braced and wrapped for poured-wall installation.
- All-vinyl frame and sash are maintenance-free — no painting or rusting.
- 3/4" insulated Low-E glass and argon gas standard for added thermal efficiency.
- Sash is double-weather-stripped to protect from outside weather infiltration.
- Full screen is removable from the inside.

Performance (all models)

U-factor: 0.27 (with Low-E glass and argon gas)

Solar Heat Gain Coefficient: 0.24

Visible Transmittance: 0.45

Condensation rating: 64

Models & Dimensions

Model	Frame W × H	Net Clear Opening (Egress) W × H	Egress Area	Net Clear Glass Area W × H	Glass Area
DWF-2745	27" × 45"	20 ¹ / ₈ " × 40 ⁷ / ₈ "	5.71 sq. ft.	20 ³ / ₈ " × 38 ³ / ₈ "	5.43 sq. ft.
DWF-3140	31" × 40"	24 ¹ / ₈ " × 35 ⁷ / ₈ "	6.01 sq. ft.	24 ³ / ₈ " × 33 ³ / ₈ "	5.65 sq. ft.
DWF-3636	36" × 36"	29 ¹ / ₈ " × 31 ⁷ / ₈ "	6.45 sq. ft.	29 ³ / ₈ " × 29 ³ / ₈ "	5.99 sq. ft.
DWF-3648	36" × 48"	29 ¹ / ₈ " × 43 ⁷ / ₈ "	8.87 sq. ft.	29 ³ / ₈ " × 41 ³ / ₈ "	8.44 sq. ft.

**Net clear opening measured with the sash opened in the normal inward operating position.*